

## LG QuantumFlux™ Pressurized UF Membrane

## Technical Service Bulletin 601


## Receipt of Modules, Short-Term Storage, and Disposal of Used Module

**Receiving Inspection**

After a shipment arrives, conduct a visual inspection of all packages to confirm that:

1. Shipment arrived without damage to the packaging or its contents.
2. All packages listed on the packing list arrived in good order.

 **CAUTION:** To avoid damage to the UF module, the UF module should not be subjected to impact, drops and excessive vibration.

 **CAUTION:** Take caution when opening the shipping container. Do not damage the membrane with the tools used to open the box.

 **CAUTION:** Two people are recommended to lift the UF module at all times

UF membrane modules are shipped in wooden crates with Styrofoam end protectors. LG Chem strongly recommends inspecting the product for any visible damage or defects immediately upon receipt. If any issues are encountered, please contact an LG Chem Customer Service representative before accepting the delivery to ensure that your rights are protected. In such cases, LG Chem will promptly identify possible causes of the damage and determine whether it occurred during transit.

Please notify your carrier or freight forwarder and a LG Chem Customer Service Representative IMMEDIATELY of any damaged merchandise or product shortages.

**Storage**

Before use, the module(s) should be stored, in their original packing, in an area between 5-40°C (41-104°F), with good ventilation, no direct sunlight, and no corrosive substances.

Allowing the module to freeze by reaching temperatures below 0°C (32°F), may cause serious damage to the membrane.

After factory performance testing, membranes are preserved in a protective solution. This prevents damage to the membrane, along with bacterial growth. Do not discharge the protective solution until you are ready to install the module.

LG Chem UF modules should NOT be stored in areas exposed to direct sunlight.

LG Chem UF modules should NOT be stored in areas where damage can occur from moving equipment such as forklifts and pallet jacks.

For long-term storage (greater than 60 days), periodically re-inspect the shipping containers to ensure that there is no physical damage or leakage. Any leakage may indicate a loss of integrity of the membrane preservative.

# Technical Service Bulletin 601

## Receipt of Modules, Short-Term Storage, and Disposal of Used Module

### Disposal of Used Module

Used LG Chem UF membrane modules should be disposed of in accordance with all local and federal regulations. Used module can be disposed of as municipal waste provided that no preservation solution or other hazardous liquids remaining within the module and no deposition of hazardous substances on the membranes at concentrations exceeding regulatory standards.

If the user wants to recycle the module, the material components by %age weight of a new module can be found below:

Material	% by Weight <sup>1)</sup>
Nitrile Rubber	0
ABS (Acrylonitrile-Butadiene-Styrene)	0.5–30
UPVC (Unplasticized Polyvinyl Chloride)	20–65
PVDF (Polyvinylidene Fluoride)	20–40
Epoxy (2Part)	2–6
Polyurethane	2–6
Silica Gel	0
Stainless Steel	4–8
EPDM (ethylene propylene diene monomer) Rubber	0.1– 0.5

<sup>1)</sup> Refers to weight of a new module

The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. LG Chem assumes no liability for results obtained or damages incurred through the application of the information contained herein. Customer is responsible for determining whether the products

and information presented are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. QuantumFlux is the Trademark of LG Chem. All rights reserved. © LG Chem, Ltd