



NF9

High rejection nanofiltration membrane

Key Features

- High rejection of salts and organic compounds such as natural organics, THM and long-chain PFAS
- Excellent fouling resistance
- Excellent durability

Main Benefits

- Great permeate water quality with low energy consumption
- Reduced cleaning frequency, chemical use, and membrane replacements

Ideal Applications

- Municipal drinking water
- Industrial water treatment
- Water reuse


Performance Specifications

Item	Unit	Value
Permeate Flow Rate	GPD (m ³ /d)	10,000 (37.9)
Minimum Salt Rejection	%	98.7
Active Membrane Area	ft ² (m ²)	400 (37)
Feed Spacer Thickness, Type	mil	34, low dP

The specifications outlined above are normalized performances based on the following test conditions:

- **Test Conditions:** 2,000 ppm MgSO₄, 70 psi (4.8 bar), 25°C (77°F), pH 7, Recovery 15%
- Permeate flow rates for individual elements may vary ±15%

Dimensions and Weight



Dimensions: mm (in)			Wet Weight: kg (lbs)
A	B	C	
Element Length	Element O.D.	Core Tube I.D.	16 (35)
1,016 (40)	200 (7.9)	28.6 (1.125)	

All dimensional information is indicative and for reference only. Please contact NanoH2O for detailed technical specifications.

Operating Specifications

Specification	Unit	Value
Maximum Applied Pressure	psi (bar)	600 (41.3)
Maximum Chlorine Concentration	ppm	< 0.1
Maximum Operating Temperature	°C (°F)	45 (113)
pH Range, Continuous Operation		2–11
pH Range, Cleaning		1–13*
Maximum Feed Water Turbidity	NTU	1.0
Maximum Feed Water SDI ₁₅		5.0
Maximum Feed Flow	gpm (m ³ /h)	75 (17)
Maximum Pressure Drop (ΔP) for Each Element	psi (bar)	15 (1.0)

* If cleaning is required outside of the recommended pH range (2–12), for example at pH 1 or 13, please contact the NanoH2O Tech Service team for consultation prior to the cleaning.

These operating specifications are for general use. For specific applications, operation at more conservative values may ensure better performance and extended membrane life. See NanoH2O Technical Bulletins for more details.



Homepage

LinkedIn

Youtube

This product is certified to
NSF/ANSI/CAN Standard 61
for drinking water systems



D-NF9-EN-013026

The product performance is expressly conditioned on Buyer's storing, installing, operating, and maintaining Product in accordance with industry accepted good practices and Seller's written instructions provided in the Seller's Technical Manual may be viewed and downloaded at www.nano2owater.com

The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. NanoH2O assumes no liability for results obtained or damages incurred through the application of the information contained

herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. All rights reserved. © NanoH2O Co., Ltd.

Please visit our website for regional contact information
www.nano2owater.com